KRX Ceiling Lamps

PRODUCT CONFIGURATIONS & SPECIFICATIONS



Butterfly-LT-108-BT-PA50/WH50R/WH30S

SIZE

W1236*D896*H200
W1530*D896*H200
W1830*D896*H200

* Aluminum alloy frame with acoustic upholstery;
* Light guide plate: Imported transparent PMMA stripes + horizontal stripes PMMA + PC diffusion film combined prism cover;
* Color rendering index>90;
* Color temperature standard:4000K;
* 1.5meter hanging rope;



Plain-LT-108-PL-PA30/36

SIZE

W1210*D43*H85
W1510*D43*H85

* Aluminum alloy frame;
* Light guide plate: Imported transparent PMMA stripes + horizontal stripes PMMA + PC diffusion film combined prism cover;
* Color rendering index>90;
* Color temperature standard:4000K;
* 1.5meter hanging rope;



Plain-LT-108-PL-PA30P/36P

SIZE

W1250*D60*H320
W1550*D60*H320

* Aluminum alloy frame with fabric upholstery;
* Light guide plate: Imported transparent PMM. stripes + horizontal stripes PMMA + PC diffusic film combined prism cover;
* Color rendering index>90;
* Color temperature standard:4000K;
* 1.5meter hanging rope;



Plain-LT-108-PL-PA78P

SIZE

W772*D60*H620

* Aluminum alloy frame with fabric upholstery;
* Light guide plate: Imported transparent PMMA stripes + horizontal stripes PMMA + PC diffusion film combined prism cover;
* Color rendering index>90;
* Color temperature standard: 4000K;
* 1.5meter hanging rope;



Moon-LT-108-MO-MO60

SIZE

W1550*D60*H320

* Aluminum alloy frame;
* Luminaire light effi ciency :approx.85LM/W;
* UGR: <17;
* Color rendering index>90;
* Color temperature standard: 4000K;
* 1.5meter hanging rope;